





Genuine Oak Specifications	240/15	190/15	190/12
Species	Oak	Oak	Oak
Coating	UV cured 7 coat Treffert lacquer system	UV cured 7 coat Treffert lacquer system	UV cured 7 coat Treffert lacquer system
Edge Profile	Micro Bevel	Micro Bevel	Micro Bevel
Surface	Subtle Brush Texture	Subtle Brush Texture	Subtle Brush Texture
Appearance	Light Feature	Feature	Feature
Finish	Ultra Matte	Ultra Matte	Ultra Matte
Locking System	Tongue & Groove (ends and sides)	Tongue & Groove (ends and sides)	Tongue & Groove (ends and sides)
Width	240mm	190mm	190mm
Thickness (Overall)	15mm	15mm	12mm
Length	2200mm	1900mm	2100mm
Packaging	5 rows per box, 1 nested row multiple boards up to 3, minimum 600mm	6 rows per box, maximum of 2 nested rows	6 rows per box, maximum of 2 nested rows
Coverage	2.64m²/carton	2.166m²/carton	2.394m²/carton
Wear Layer	4mm	4mm	2mm







*Colours available in Genuine Oak 190/12 size.



WHITEHAVEN





HAMPTONS



*WHITE WASH



*NATURAL CLEAR



WESTERN



DISTRESS



*SMOULDERED



*URBAN



BARREL



*VINTAGE



ASH



STERLING



SMOKEY



*NUAGE



CHOCOLATE



*SLATE GREY



CONTRAST



TUXEDO



RAW (240/15 and 190/15 Only)





Auckland

Unit 11/18 Corinthian Drive, Albany, Auckland 0632 BY APPOINTMENT ONLY Phone: 0800 HURFORD (0800 4873673) info@hurfordflooring.co.nz



50 Hull Road, Mt Maunganui, New Zealand, 3150 Phone: 0800 HURFORD (0800 4873673) info@hurfordflooring.co.nz









Proud to be a Member of

