











Oaks Aussie Species Tiles



QUATTRO04

TECHNICAL SPECIFICATIONS

Plank Size 228 x 1520mm

QUATTRO09

Total Thickness 6mm (4mm board & 1.50mm backing)

Wear Layer 0.50mm

Wear Layer Treatment Quartz enhanced PUR coating

Surface Natural embossed, true to life oak boards

Edge Design Micro V groove 4 sided

Fire Rating ISO 9239.1

QUATTRO03

Slip Rating

QUATTRO01

Underfloor Heating

Planks per Box

Installation Method

Warranty

Suitable all areas

РЗ

Suitable for water based systems

6 pcs/box (2.079m²)

5G - no underlay required

25 Yr Residential, 10 Yr Commercial

- installs directly over irregularities and existing floors
- can be laid over ceramic and porcelain tiles
- can be laid over concrete
- can be laid over chipboard and tongue & groove flooring
- existing floors need to adhere to the sub-floor
- existing floor cannot be cushioned
- uneven floors require sub-floor preparation when there is a height variation more than 3mm over 1m*
- sub-floors should be clean and dry
- * Please refer to installation guidelines; if uncertain see clarification prior.









au 03 9401 0888 nz 0800 150 555 signaturefloors.com.au signaturefloors.co.nz

Terms & Conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms & Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification.